

## Voorbeeld van een werkende 3CX SIP trunk installatie met voicedeals.nl

Omdat VoiceDeals nog niet standaard ondersteund wordt vanuit 3CX maken we gebruik de Generic SIP Trunk. Vooral de settings voor de outbound parameters zijn belangrijk om je telefoonnummer bij uitgaande gesprekken juist mee te geven.

### Tabblad General

name for Trunk:	Generic SIP Trunk
Registrar/Server/Gateway Hostname or IP:	sip.voicedeals.nl Port: 5060
Outbound Proxy:	laat standaard leeg Port: 5060
Number of SIM Calls:	10
Type of Authentication:	Register/Account based
Authentication ID (aka SIP User ID):	Het userID zoals gekregen van voicedeals
Authentication Password:	Het password zoals gekregen van voicedeals
3 Way Authentication:	niet selecteren
Main Trunk No:	Het te gebruiken hoofdnummer van de telefoonnummers die je ontvangen hebt van voicedeals
Destination for calls during office hours:	de keuze waar je dit nummer naar toe wilt leiden
Destination for calls outside office hours:	de keuze waar je dit nummer naar toe wilt leiden

### Tabblad DIDs

Geef hier alle nummer op zoals je deze gekregen hebt van Voicedeals. Bijvoorbeeld met een 085 nummer geeft je op In het format 3185.....

### Tabblad Caller ID

Configure Outbound Caller ID: Geef hier weer het hoofdnummer op zoals je ook hebt opgegeven in Main Trunk No in het tabblad General

Inbound en Outbound patterns kun je leeg laten.

### Tabblad Options

Deze instellingen kun je default laten staan. Default zijn de opties Allow inbound calls, Allow outbound calls, Disallow video calls en PBX Delivers Audio geselecteerd. Re-Register Timeout staat op de waarde 600.

## Tabblad Inbound Parameters

### Settings:

"CallerNum" caller's number (default: From->user)	From: User Part
"CalledNum" number that has been dialed (default: To->user)	To: User Part
"CallerName" caller's name (default: From->display name)	From User Part

Call Source Identification is geselecteerd

### Settings:

Contact: Host Part "GW HostPort" gateway/provider host/port  
Use both "Source Identification" rules and ..... is niet geselecteerd

## Tabblad Outbound Parameters

### Settings:

Request Line URI : User Part	"CalledNum" number that has been dialed (default: To->user)
Request Line URI : Host Part	"GWHostPort" gateway/provider host/port
Contact: User Part	"OriginatorCallerID" Original Caller number will be sent
Contact: Host Part	"ContactUri" usually, content of Contact field
To: Display Name	"CallerName" name that has been dialed (default: To-> display name)
To: User Part	"CalledNum" number that has been dialed (default: To->user)
To: Host Part	"GWHostPort" gateway/provider host/port
From : Display Name	"OriginatorCallerID" Original Caller number will be sent
From : User Part	"OriginatorCallerID" Original Caller number will be sent
From : Host Part	"GWHostPort" gateway/provider host/port
User Agent: Tekst String	Leave default value
Remote Party ID - Called Party : Display Name	Leave default value
Remote Party ID - Called Party : User Part	Leave default value
Remote Party ID - Called Party : Host Part	Leave default value
Remote Party ID - Calling Party : Display Name	"CallerName" caller's name (default: From-> display name)
Remote Party ID - Calling Party : User Part	Leave default value
Remote Party ID - Calling Party : Host Part	"GWHostPort" gateway/provider host/port
P-Asserted Identity : Display Name	Leave default value
P-Asserted Identity : User Part	Leave default value
P-Asserted Identity : Host Part	Leave default value
P-Preferred Identity : Display Name	Leave default value
P-Preferred Identity : User Part	Leave default value
P-Preferred Identity : Host Part	Leave default value
P-Called-Party-ID : Display Name	Leave default value
P-Called-Party-ID : User Part	Leave default value
P-Called-Party-ID : Host Part	Leave default value